



AMB
Tronic[®]

the power to lead



Server



Telecom



Industrial



Network




Hospitality



Medical

AMB INVS- Series





- Pure sine wave inverter
- Output power factor 1 (only 0.8 for 3KP/5KP models)
- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/solar input priority via LCD setting
- Compatible to AC mains or generator power
- Battery equalization for optimized battery performance and lifecycle
- Parallel operation with up to 9 units only available for INVS 3KP/4KVA/5KVA/5KP*

➤ SPECIFICATION

MODEL	INVS 1K-12	INVS 2K-24	INVS 3K-24	INVS 3KP-24	INVS 4K	INVS 5K	INVS II 5K	INVS 5KP
Rated Power	1000VA/ 1000W	2000VA/ 2000W	3000VA/ 3000W	3000VA/ 2400W	4000VA/ 4000W	5000VA/ 5000W	5000VA/ 5000W	5000VA/ 4000W
Parallel Capability	No	No	No	Yes, 9 units	Yes, 9 units	Yes, 9 units	Yes, 9 units	Yes, 9 units
INPUT								
Voltage	230 VAC							
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)							
Frequency Range	50 Hz/60 Hz (Auto sensing)							
OUTPUT								
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%							
Surge Power	2000VA	4000VA	6000VA		8000VA	10000VA		
Efficiency (Peak)	90% - 93%	93%		90%	93%	93%	90%	90%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)							
Waveform	Pure sine wave							
BATTERY								
Battery Voltage	12 VDC (24VDC and 48VDC versions are also available)	24 VDC	24 VDC (48VDC version is also available)	24 VDC	48 VDC		24 VDC	
Floating Charge Voltage	13.5 VDC	27 VDC	27 VDC	27 VDC	54 VDC	54 VDC (optional 64VDC, please check with sales)	54 VDC	27 VDC
Overcharge Protection	15.5 VDC	31 VDC	31 VDC	30 VDC	60 VDC	60 VDC (optional 66VDC, please check with sales)	66 VDC	30 VDC
SOLAR CHARGER & AC CHARGER								
Maximum PV Array Power	500 W	600W	600W	1000W	4000W	4500W	2000W	
MPPT Range @ Operating Voltage	15 VDC ~ 80 VDC	30 VDC~ 66 VDC	30 VDC~ 66 VDC	30 VDC~ 80 VDC	60 VDC~ 115 VDC	120 VDC~ 430 VDC	30 VDC~ 115 VDC	
Maximum PV Array Open Circuit Voltage	102 VDC	75VDC	75VDC	100VDC	145 VDC	450 VDC	145 VDC	
Maximum Solar Charge Current	40A	25A	25A	40A	80 A	80 A	80A	
Maximum AC Charge Current	20A	30A	30A	60A	60 A	80 A	60A	
Maximum Charge Current	60A	55A	55A	100A	140 A	80 A	140A	
PHYSICAL								
Dimension,DxWxH (mm)	95 x 240 x 316	100 x 272 x 355		100 x 272 x 385	120 x 295 x 468		180 x 310 x 475	
Net Weight (kgs)	5.2	7.0	7.4	7.5	12.5	13.5	11	12.5
ENVIRONMENT								
Humidity	5% to 95% Relative Humidity (Non-condensing)							
Operating Temperature	0°C to 55°C							
Storage Temperature	-15°C to 60°C							

* Typical transfer time for parallel operation is 30ms.

** Optional remote panel is NOT available for INVS 3KP-24 / INVS II 5K / INVS 5KP
Product specifications are subject to change without further notice.